

5-in1 XVR

16 CHANNEL



Product Features:

- Standard compression format with efficient processing and clear image
- Support AHD,TVI,CVI,IPC,960H Hybrid Mode
- Two high-speed USB2.0 interfaces
- Backup, mobile monitoring, PTZ control.
- 16 Video and 8 Audio support
- Metal body with 2 SATA HDD slot
- A powerful mobile control and monitoring features to support Android, iPhone etc
- User friendly GUI

16CH 1080N (5 in 1; AHD, CVI, TVI, 960H and IP)

AHD standard HD BNC interface

Support HD video signal recording, storage, playback and transport

| | | |
|-------------------------|---|---|
| Model | RX-160802-ECO | |
| Compression | H.264 Standard compression | |
| Operation | Embedded Linux | |
| Dual stream | Can be set up in each channel | |
| Monitor image quality | 1080N(960×1080) | |
| Image dynamic detection | Multiple detection areas in each channel | |
| Video Frame Rate | 1080N 15FPS/CH | |
| Hybrid Mode | 1.AHD / TVI / CVI:16CH 1080N@15fps recording, 4CH 1080N playback ; 2.AHD / TVI / CVI:16CH 1080N@12fps recording, 16CH 1080N12FPS playback 3. HVR:8CH 1080N@15fps Analog + 8CH 1080P@25fps IP recording, 2CH 1080P@25fps playback ; 4.NVR:16CH 960P@25fps IP recording, 4CH 960P@25fps playback ; 5.NVR:4CH 3M@25fps IP recording, 4CH 3M@25fps playback ; 6.NVR:4CH 5M@25fps IP recording, 2CH 5M@25fps playback ; | |
| Video mode | Support manual, automatic, dynamic monitoring, alarm trigger video mode | |
| Upgrade / Backup | USB DISK, Network | |
| Operate mode | Mouse | |
| Save recording | local hard disk and network | |
| External interface | Video input | 1080N@15FPS total 240FPS |
| | Audio input | 8×RCA |
| | Video output | 1*VGA,1*HDMI , 1*CVBS |
| | Audio output | 1×RCA |
| | Network interface | 10M/100M base-T Ethernet (RJ-45) |
| | USB connect port | 2 x USB 2.0 |
| | RS485 | RS485*1 |
| | Alarm input | 4CH |
| | Alarm output | 1CH |
| Hard disk | Internal HDD | 2 SATA HDD port with 4 TB capacity each |
| Cell phone monitoring | Support iPhone,iPad, Android and 3G-4G | |
| Power | 12V/4A | |
| Operating Temperature | -10°C~ +55°C | |
| Operating humidity | 10%-90% | |
| DVR size | 335*250*50mm | |
| Weight | <2.60kg(without HDD) | |