

## 5-in1 XVR

## 4 CHANNEL



### Product Features:

- Standard compression format with efficient processing and clear image
- Support AHD,TVI,CVI,IPC,960H Hybrid Mode
- Two high-speed USB2.0 interfaces
- Backup, mobile monitoring, PTZ control.
- 4 Video and 1 Audio support
- Metal body
- A powerful mobile control and monitoring features to support Android, iPhone etc
- User friendly GUI

## 4 CH 1080N (5 in 1; AHD, CVI ,TVI,960H and IP)

AHD standard HD BNC interface

Support HD video signal recording, storage, playback and transport

Model	<b>RX-040101-Lite</b>	
Compression	H.264 Standard compression	
Operation	Embedded Linux	
Dual stream	Can be set up in each channel	
Monitor image quality	1080N(960×1080)	
Image dynamic detection	Multiple detection areas in each channel	
Video Frame Rate	1080N 25FPS/CH	
Image playback quality	1080N TOTAL:100 FPS(4 CH)	
Hybrid Mode	<b>1.AHD / TVI / CVI:4CH 1080N@25fps recording, 4CH6fps 1080N playback</b> <b>2. HVR:2CH 1080N@25fps Analog + 2CH 1080P@25fps IP recording, 1CH 1080P@25fps playback ;</b> <b>3.NVR:4CH 1080P@25fps IP recording, 1CH 1080P@25fps playback ;</b>	
Video mode	Support manual, automatic, dynamic monitoring, alarm trigger video mode	
Upgrade / Backup	USB DISK, Network	
Operate mode	Mouse	
Save recording	local hard disk and network	
External interface	Video input	1080N@25FPS total 100FPS
	Audio input	<b>1×RCA</b>
	Video output	<b>1*VGA,1*HDMI , 1*CVBS</b>
	Audio output	<b>1×RCA</b>
	Network interface	10M/100M base-T Ethernet (RJ-45)
	USB connect port	2 x USB 2.0
	RS485	RS485*1
	Alarm input	NA
	Alarm output	NA
Hard disk	Internal HDD	1 SATA HDD port with 4 TB capacity each
Cell phone monitoring	Support iPhone,iPad, Android and 3G-4G	
Power	<b>12V/2A</b>	
Operating Temperature	-10°C~ +55°C	
Operating humidity	10%-90%	
DVR size	250*230*45mm	
Weight	<1.6kg(without HDD)	